

AIO X

Technical Specification

Detection Capabilities

Footsteps Detection	Up to 12m/39ft radius
Vehicle Detection	Up to 25m/82ft radius
Digging Detection	Up to 25m/82ft radius
Detection Zone	360° coverage

Communication

RF Frequency	433Mhz (Default), 868/915Mhz (Optional)
Network Protocol	LoRa (Long Range) low-power wide-area network
Transmission Range (Antenna 2cm below ground)	Up to 250m/820ft radius
Transmission Range (Antenna 5cm above ground)	Up to 1Km/3,280ft radius

Environmental & Power

IP Rating	IP68 (MIL-STD 810G)
Operating Temperature	-40°C to 85°C / -40°F to 185°F
Battery Life	Non-rechargeable, 6 years

Physical Specifications

Dimensions (Sensor)	103mm × 103mm × 150mm / 4" × 4" × 5.9"
Dimensions (Spike)	75mm / 2.95"
Weight	500g / 1.1lbs
Installation Depth	30-50cm / 11.8"-19.6"



Overview

AIO X buried sensor is a wireless seismic sensor designed for long term installations of commercial applications (residential security). The sensor includes internal non-rechargeable battery for up to 6 years of continuous operation.



Components

- Top part: battery pack & DSP processor (sealed)
- Bottom part: sensing element and cable
- Spike



Specifications subject to change without notice. ©2026 SensoGuard Ltd.